

1	2	3	4	5	6	7	8

A	<p>2.54*No.of Contacts/2+0.50±0.30</p>						
B	<p>Current Rating: 3 Amps          Insulator Resistance: 1000 Megohms min          Contact Resistance: 20 m ohms max          Dielectric Withstanding: AC 500 V          Operating Temperature: - 40° ~ +85° C          Contact Material: Brass          Insulator Material: Polyester, UL 94V-0          Standard: PBT          Finish: Tin, Gold Plated          Standard: Gold Flash all over          Note: Duplex Plating: Gold Plated on contact area, Tin on solder area          Insulator Material: Polyester, UL 94V-0          Max Processing Temp: 230° C for 60 seconds          Max Processing Temp: 260° C for 10 seconds</p>						

C	<p>2.54*No.of Contacts/2-2.54</p> <p>Dim.G 10.10</p> <p>Dim.A 3.20</p>						
D	<p>Recommended P.C. Board SMD Layout</p> <p>2.54*No.of Contacts/2-2.54</p> <p>φ1.02</p>						

E	<p>1. Insulator material: 6. Contact Plated: 7.Special Options</p> <p>A=PBT N=PA6T T=Matte Tin over Nickel          L=LCP P=PA9T W=Matte Tin over nickel 150μ"          2. A=Phosphor Bronze Y=Bright Tin over Nickel          B=Brass C = Putin          3. Per Row:02-40PIN F = Gold Flash, Matte Tin 100μ"          4. Tail Style: A=Gold 3μ" M=Gold 15μ" , Matte Tin 100μ"          R0=90° U = Gold 30μ" V=Gold 30μ" , Matte Tin 100μ"          BK=Black D = Gold 5μ" H = Contact area 1U " , Other areas 0.8U"</p>																																						
F	<p>(RoHS Compliant) P1 X 57 X - 2 XX R0 BK X 000 X</p> <p>1 2 3 4 5 6 7 8</p>																																						
<table border="1"> <tr> <td colspan="2"> <p>东莞市震升电子有限公司 DONG GUAN ZHEN SHENG ELECTRONICS CO., LTD</p> </td> <td colspan="2">PART NO.</td> <td colspan="2">P1X57X-2XXR0BKX000X</td> <td colspan="2">.X .XX .XXX ±0.30 ±0.20 ±0.1</td> </tr> <tr> <td colspan="2">BOM</td> <td colspan="2">DRAWING NO</td> <td colspan="2">ZS-00104-M</td> <td colspan="2">EDITION: A1</td> </tr> <tr> <td colspan="2">3:P157B-R30-Y01-C11</td> <td colspan="2">DRAWN BY</td> <td colspan="2">Deng jin quan</td> <td colspan="2">2023-04-2</td> </tr> <tr> <td colspan="2">TEL:0769-85305015 FAX:0769-85845060</td> <td colspan="2">APPROVAL BY</td> <td colspan="2">Chen xiao guang</td> <td colspan="2">2022-04-03</td> </tr> </table>								<p>东莞市震升电子有限公司 DONG GUAN ZHEN SHENG ELECTRONICS CO., LTD</p>		PART NO.		P1X57X-2XXR0BKX000X		.X .XX .XXX ±0.30 ±0.20 ±0.1		BOM		DRAWING NO		ZS-00104-M		EDITION: A1		3:P157B-R30-Y01-C11		DRAWN BY		Deng jin quan		2023-04-2		TEL:0769-85305015 FAX:0769-85845060		APPROVAL BY		Chen xiao guang		2022-04-03	
<p>东莞市震升电子有限公司 DONG GUAN ZHEN SHENG ELECTRONICS CO., LTD</p>		PART NO.		P1X57X-2XXR0BKX000X		.X .XX .XXX ±0.30 ±0.20 ±0.1																																	
BOM		DRAWING NO		ZS-00104-M		EDITION: A1																																	
3:P157B-R30-Y01-C11		DRAWN BY		Deng jin quan		2023-04-2																																	
TEL:0769-85305015 FAX:0769-85845060		APPROVAL BY		Chen xiao guang		2022-04-03																																	