



A	<p>Current Rating: 3 Amps</p> <p>Insulator Resistance: 1000 Megohms min</p> <p>Contact Resistance: 20 m ohms max</p> <p>Dielectric Withstanding: AC 500 V</p> <p>Operating Temperature: - 40° ~ +85° C</p> <p>Contact Material: Brass</p> <p>Insulator Material: Polyester, UL 94V-0</p> <p>Standard: PBT</p> <p>Finish: Tin, Gold Plated</p> <p>Standard: Gold Flash all over</p> <p>Note:</p> <p>Duplex Plating: Gold Plated on contact area, Tin on solder area</p> <p>Insulator Material: Polyester, UL 94V-0</p> <p>Max Processing Temp: 230° C for 60 seconds</p> <p>Max Processing Temp: 260° C for 10 seconds</p>																												
B	<p>Recommended P.C. Board SMD Layout</p>																												
C	<p>1. Insulator material: A=PBT N=PA6T L=LCP P=PA9T 2. A=Phosphor Bronze B=Brass 3. Per Row: 02-40PIN 4. Tail Style: S0=180° 5. Color: BK=Black</p> <p>6. Contact Plated: T=Matte Tin over Nickel W=Matte Tin over nickel 150μ" Y=Bright Tin over Nickel C = PutIn F = Gold Flash, Matte Tin 100μ" A=Gold 3μ" B=Gold 3μ" D = Gold 5μ"</p> <p>7. Special Options I = gold plated 1 μ E=Gold 5μ" G=Gold 10μ" J=Gold 10μ" L = Gold 15μ" M=Gold 15μ" U = Gold 30μ" V=Gold 30μ" H = Contact area 1U" Other areas 0.8U"</p> <p>8. Packing: A=Bag B=Tube C=Tray D=Small box E=Cap+Reel F=Cap+tube I=Mylar+Reel</p>																												
D	<p>1. Insulator material: A=PBT N=PA6T L=LCP P=PA9T 2. A=Phosphor Bronze B=Brass 3. Per Row: 02-40PIN 4. Tail Style: S0=180° 5. Color: BK=Black</p> <p>6. Contact Plated: T=Matte Tin over Nickel W=Matte Tin over nickel 150μ" Y=Bright Tin over Nickel C = PutIn F = Gold Flash, Matte Tin 100μ" A=Gold 3μ" B=Gold 3μ" D = Gold 5μ"</p> <p>7. Special Options I = gold plated 1 μ E=Gold 5μ" G=Gold 10μ" J=Gold 10μ" L = Gold 15μ" M=Gold 15μ" U = Gold 30μ" V=Gold 30μ" H = Contact area 1U" Other areas 0.8U"</p> <p>8. Packing: A=Bag B=Tube C=Tray D=Small box E=Cap+Reel F=Cap+tube I=Mylar+Reel</p>																												
E	<p>1. Insulator material: A=PBT N=PA6T L=LCP P=PA9T 2. A=Phosphor Bronze B=Brass 3. Per Row: 02-40PIN 4. Tail Style: S0=180° 5. Color: BK=Black</p> <p>6. Contact Plated: T=Matte Tin over Nickel W=Matte Tin over nickel 150μ" Y=Bright Tin over Nickel C = PutIn F = Gold Flash, Matte Tin 100μ" A=Gold 3μ" B=Gold 3μ" D = Gold 5μ"</p> <p>7. Special Options I = gold plated 1 μ E=Gold 5μ" G=Gold 10μ" J=Gold 10μ" L = Gold 15μ" M=Gold 15μ" U = Gold 30μ" V=Gold 30μ" H = Contact area 1U" Other areas 0.8U"</p> <p>8. Packing: A=Bag B=Tube C=Tray D=Small box E=Cap+Reel F=Cap+tube I=Mylar+Reel</p>																												
F	<p>东莞市震升电子有限公司 DONG GUAN ZHEN SHENG ELECTRONICS CO., LTD</p> <table border="1"> <tr> <td>BOM 1:</td> <td>P1N85-140BKHC1</td> <td>PART NO.</td> <td>P1X85X-1XXS0BKX000X</td> <td>.X</td> <td>.XX</td> <td>.XXX</td> </tr> <tr> <td>2:</td> <td>P185B-S30-Y00-C11</td> <td>DRAWING NO</td> <td>ZS-00088-M</td> <td>±0.30</td> <td>±0.20</td> <td>±0.1</td> </tr> <tr> <td>3:</td> <td></td> <td>DRAWN BY</td> <td>Deng jin quan</td> <td>EDITION: A1</td> <td>ITEM: P1</td> <td>SCALE: 1:1</td> </tr> <tr> <td colspan="3">TEL: 0769-85305015 FAX: 0769-85845060</td> <td>APPROVAL BY</td> <td>Chen xiao quang</td> <td>2022-04-03</td> <td>UNIT: M:M</td> </tr> </table>	BOM 1:	P1N85-140BKHC1	PART NO.	P1X85X-1XXS0BKX000X	.X	.XX	.XXX	2:	P185B-S30-Y00-C11	DRAWING NO	ZS-00088-M	±0.30	±0.20	±0.1	3:		DRAWN BY	Deng jin quan	EDITION: A1	ITEM: P1	SCALE: 1:1	TEL: 0769-85305015 FAX: 0769-85845060			APPROVAL BY	Chen xiao quang	2022-04-03	UNIT: M:M
BOM 1:	P1N85-140BKHC1	PART NO.	P1X85X-1XXS0BKX000X	.X	.XX	.XXX																							
2:	P185B-S30-Y00-C11	DRAWING NO	ZS-00088-M	±0.30	±0.20	±0.1																							
3:		DRAWN BY	Deng jin quan	EDITION: A1	ITEM: P1	SCALE: 1:1																							
TEL: 0769-85305015 FAX: 0769-85845060			APPROVAL BY	Chen xiao quang	2022-04-03	UNIT: M:M																							